

Content

1 Device - Revision Record / What is new?..... 1
 1.1 Hardware 1
 1.2 Software..... 1
2 DTM - Engineer IT Device Type Manager 1
 2.1 Supported devices 1
 2.2 Version record / What is new? 1
 2.3 Requirements 1
 2.3.1 PC-Hardware, Operating system 1
 2.3.2 Frame application / compatibility 1
 2.3.3 Software package contents 1
 2.4 Installation and configuration 2
 2.4.1 Installation..... 2
 2.4.2 Installed files 2
 2.4.3 Uninstall instructions 2
 2.5 Update- / Upgrade instructions 2
 2.6 Known problems and limitations 2
 2.7 Getting help / further information 2
 2.8 How to get the Software (driver)? 2
 2.9 Licensing the DTM..... 2

1 Device - Revision Record / What is new?

1.1 Hardware

Released Revision	Released Date	Remarks
...
--	2004	Current Revision

1.2 Software

Released Revision	Released Date	Remarks
...
1.39	03/2004	
1.42	11/2005	Latest revision enhancements for PROFIBUS

2 DTM - Engineer IT Device Type Manager

2.1 Supported devices

– CONTRAC with device Software revision ≤ X.35

2.2 Version record / What is new?

Compatible with FDT 1.2 frame applications.

Released Version	Released Date	Remarks
01.01.03	09.02.2004	Furst release, FDT1.2 kompatibel
04.02.03	11/2005	Implementation "silent setup"
04.02.04	14.02.2006	Bugfixing

2.3 Requirements

2.3.1 PC-Hardware, Operating system

- Minimum requirement
 Intel Pentium III Processor 450 MHz or compatible.
 256 MB RAM memory.
 300 MB free hard disk space.
 Windows 2000 / XP.
 Internet Explorer 5.0.
 Adobe Reader latest version
 full administrator rights.
 The ABB FDT1.2 DTM CONTRAC-HART is released for Windows2000 and Windows XP

2.3.2 Frame application / compatibility

The ABB FDT 1.2 DTM CONTRAC-HART is released for DSV401 (SMART VISION) Release 3

The FDT compatibility was tested with the dtmINSPECTOR Rev. 1.01.21. Therefore the ABB DTM should be usable in all Frame Applications according the requirements of FDT 1.2. Please read also the respective Frame Application documentation.

2.3.3 Software package contents

The setup files are in the respective DTM sub directory
 – setup.exe

2.4 Installation and configuration

2.4.1 Installation

- Make sure that the minimum hardware requirements are met.
- Start Windows (with administrator rights!).
- Cancel all running programs.
- Insert CD-ROM.
- Start "Setup.exe" in the DTM\DTM CONTRAC-HART directory of the CD or in the folder you choosed for the software uploaded from the Internet.
- Follow the instructions.

2.4.2 Installed files

2.4.3 Uninstall instructions

For uninstalling in the operating system: Start-> Settings
-> Control Panel -> Add/Remove Programs -> Install/Uninstall"
-> Select the DTM and Uninstall.
In any case first uninstall all DTMs before uninstalling the frame application SMART VISION

2.5 Update- / Upgrade instructions

- Uninstallation is not needed before update / upgrade. It can be handled like a new installation, existing projects will be kept.
- Hints regarding new versions may be found under <http://www.abb.com/Fieldbus>

2.6 Known problems and limitations

- Entries in edit boxes have to be acknowledged by Enter or TAB to be valid.
- If starting of a DTM fails with a runtime error 6 which occurs together with a control SV4_digital.OCX, the PC needs to reboot.

2.7 Getting help / further information

- Press "F1" for online help. Help concerning the implementation of the DTM in the system environment (e.g. SMART VISION, AC800F, CMC60, CMC70) can be found in the respective documentation.

Hints regarding commissioning

- Initialisation of the DTM for the CONTRAC:
For starting the DTM, the DTM for the CONTRAC as HART device has to be used when creating the project tree. For initialisation the point "More" has to be selected in the menu under "Device". Depending on the operating speed of the PC this could take some seconds.

- Configuration of the CONTRAC:
The DTM is started by clicking the right mouse key or via the menu point "Device", in each case with "Edit".
When an online connection has been established it is now recommended to make an upload.
- When a device has been connected for the first time, and an upload has been done, it is recommended to save all data using the menu file/save as dataset. (database suffix *.dat)

2.8 How to get the Software (driver)?

Please use one of the following ways to get the Software (driver):

- Available on the newest DSV4xx (SMART VISION) & DTM CD-ROM
- As download from <http://www.abb.com/Fieldbus>
 - >[select Fieldbus protocol]
 - >[select field device]
 - >[select device group / name]
 - use link read more / downloads
 - > go to flag "Fieldbus & HART Files"
- The Aspect Object (*.afw) online file contains all driver and information. For the *.afw file
 - > go to flag "Downloads"

2.9 Licensing the DTM

- The DTM is usable unlimited without any license in every Frame Application.

**TABB has Sales & Customer Support
expertise in over 100 countries worldwide.**

<http://www.abb.com/instrumentation>

The Company's policy is one of continuous product improvement and the right is reserved to modify the information contained herein without notice.

Printed in the Fed. Rep. of Germany (01.2006)

© ABB 2006



ABB Ltd.
Salterbeck Trading Estate
Workington, Cumbria
CA14 5DS
UK
Tel: +44 (0) 1946 830 611
Fax: +44 (0) 1946 832 661

ABB Inc.
125 E. County Line Road
Warminster, PA 18974
USA
Tel: +1 215 674 6000
Fax: +1 215 674 7183

ABB Automation Products GmbH
Schillerstr. 72
32425
Germany
Tel: +49 551 905-534
Fax: +49 551 905-555