

FlexGripper - Claw Palletizing gripper

The FlexGripper - Claw is a simple plug-and-play extension to the ABB IRB 460 or IRB 660 palletizing robots for high-speed bag palletizing applications. Stainless steel parts make it perfect for use even in the harshest conditions.



Wide-ranging flexibility

The IRB 660 and the compact IRB 460 palletizing robots can be made even more effective for bag palletizing applications with the addition of the FlexGripper - Claw. Ideal for use in even the harshest conditions involving chemicals and salt, the FlexGripper-Claw can handle bag weights up to 50 kilograms and varying bag shapes and contents - from rice to gravel, and from plastic to cement.

Easy to integrate, easy to use

The FlexGrippers are easy to install and program. The robot HMI, FlexPendant, comes pre-configured with FlexGripper input/output signals which greatly reduces both set up and programming time. And the graphical user interface simplifies the testing of palletizing routines. For example a FlexGripper pick-and-place test can be carried out with just a single click.

Faster, more accurate programming

ABB's range of palletizing robots and FlexGrippers are also

fully supported by the RobotStudio Palletizing PowerPac. This user-friendly, PC based software, comes pre-configured with all ABB robots and gripper models. It allows users who have little or no robot programming experience to create programs and simulations, and design complete palletizing installations. This enables a palletizing system to be configured rather than programmed, and saves up to 80 percent in commissioning time.

Speed and precision

The FlexGripper-Claw uses pressure plates to ensure the bags are moved with speed and precision. It comes complete with all air hoses and signal cables and is ready to plug-and play on your chosen robot model.

Unrivalled experience and global support

With more than 25 years of experience in the palletizing sector, ABB has a sales and service organization in 53 countries and over 100 locations.

FlexGripper - Claw

Highlighted features

- For high speed bag palletizing up to 50 kg payloads.
- Pneumatically actuated mechanism to clamp a bag from the sides.
- Bag centering plates provided with 200 mm adjusting stroke for different bag sizes.
- Clamp pads that contact the top of the bag to hold it in position.
- All bag contacting parts made in stainless steel.
- Robot mounting plate for IRB 460 and IRB 660 included.
- Completely assembled with hoses and cables and ready to plug and play.
- Graphical User Interface (GUI) provided on robot FlexPendant for easy gripper setup, tuning, and production monitoring.

Main applications

Bag palletizing

Specification

Handled products	1
Max. weight per lift	50 kg
Gripper weight	60 kg
Finger pitch	80 mm
Bag height range	120 - 250 mm
Bag length range	300 - 750 mm
Bag width range	250 - 450 mm
Cable rotation range	+ - 180°
Air pressure	4-6 bar

