Rev Ind	Revision	Appd	Date
1		TL	01-38





OUTER TERMINAL



INNER TERMINAL FOR STRANDED CABLE



END SHIELD



SOLID ROD CONNECTOR



The solid rod can be divided either:
Alt.1: 20mm below the bushing flange or
Alt.2: 20mm below the upper end of the bottom porcelain

Bushing Data:

Rated Voltage	52	kV
Phase to Ground Voltage	52	kV
Dry Lightning Impulse 1,2/50µs	250	kV
Wet power frequency AC	105	kV
Routine test 1min dry 50Hz	120	kV
Rated Current	1250	A
Creepage Distance	1500±50	mm
Creepage Distance Protected	580	mm
Mass	30	kg

Ordering Data:

BUSHING	COLOUR AIR INSULATOR
LF123168-K	BROWN
-L	LIGHT GREY

OUTER TERMINAL

LF 170 002-B	Cu, Ø30, L=125
LF 170 001-B	Al, Ø30, L=125

OTHER TYPES ON REQUEST

INNER TERMINAL FOR STRANDED CABLE

For brazing	Conductor area	D1
LF 170 011-T	up to 285mm²	Ø29
LF 170 011-V	Undrilled with pilot hole	Ø5

SOLID ROD CONNECTOR

LF 170 052 -BF for Alt.1

LF 170 052 -BD for Alt.2

ABB Components	Ludvika, Sweden
No.	
Ur-Uy	kV Ir A 50-60 Hz
Li / Si / AC	kVp
M	kg L mm V
C1	pF Tan δ x
C2	pF Tan δ x

Based on	Reg. No.	Title	
		GOB 250-1250-0.3 WITH OIL LEVEL GAUGE SHORT END SHIELD	
Prepared: Lövnord	Responsible department: COM/BK 0036		
Approved: Johansson	Take over department		Language
Design engineering review: Gudmundsson	Database		Page: 1(1)
ABB Components		Document No.: 2751369-177	

We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©ABB