


MULTI-FUNCTION OVERCURRENT AND DIR. EARTH-FAULT PROTECTION



101 RXTUG 22H
107 RXHL 422

- 1), 2) BINARY INPUT, PROGRAMMABLE
- 3)-7) RELAY OUTPUTS 1-5, PROGRAMMABLE FUNCTION
- 8) LOSS OF AUXILIARY VOLTAGE

PROGRAMMABLE FUNCTIONS FOR BINARY INPUTS:
BLOCKING/ENABLING I>, I>>, I>>>, DIR IN>, DIR IN>>, DIR IN>>>;
THERMAL RESET 0, BREAKER FAILURE EXTERNAL START,
ALTERNATIVE SETTINGS; RESET OF LED INDICATIONS.

PROGRAMMABLE FUNCTIONS FOR BINARY OUTPUTS:
START AND TRIP I>, I>>, I>>>, DIR IN>, DIR IN>>, DIR IN>>>;
THERMAL ALARM 0; THERMAL TRIP 0;
BREAKER FAILURE RE-TRIP; BREAKER FAILURE BACK-UP TRIP;
ALTERNATIVE SETTINGS; IN SERVICE

BINARY INPUT OPTIONS:
CIRCUIT-BREAKER CLOSED; CIRCUIT-BREAKER READY;
BLOCKING OF AUTORECLOSING; AUTORECLOSING EXTERNAL ON.

BINARY OUTPUT OPTIONS:
AUTORECLOSING ON; AUTORECLOSING READY;
AUTORECLOSING STARTED;
AUTORECLOSING PULSE TO CIRCUIT-BREAKER;
AUTORECLOSING UNSUCCESSFUL; INTENTIONAL OVERREACH TRIP.

We reserve all rights in this document and in the information contained therein. Reproductions, use or distribution of this document without the written consent of ABB Automation Technologies AB is strictly forbidden.

Customer drw no	Prep. PTUA/ TPTD H Raza/JE 2000-03-22	Connection Diagram	Cont. sh/ No of sh
	Appr. PTUA/ Roger Karlsson 2000-03-31		
	Resp. dept PTUA/ TPTD	Document number	Lang.
		1MRK001995-AAA	en
Based on	ABB ABB Automation Technologies	Rev.	Sheet
		-	1

Document status: Approved